# **SPECIFICATION DATA**

## 1. Product Name

VERSI-FOAM® Systems 10 and 33 Disposable Foam Kit

## 2. Manufacturer

RHH FOAM SYSTEMS, INC. 6001 South Pennsylvania Avenue Cudahy WI 53110 USA Telephone: 1-800-657-0702 414-744-6066 FAX: 414-744-8227 E-Mail: sales@rhhfoamsystems.com Web Site: www.rhhfoamsystems.com

## 3. Product Description

VERSI-FOAM® Systems 10 and 33 are disposable foam kits that contains two chemical components - Component A (isocyanate) and Component B (polyol blend); patented U-CONTROL dispensing gun, ten (10) multi-purpose mixing nozzles, and packet of petroleum jelly. It requires no external power source.

### 4. Technical Data

VERSI-FOAM Systems 10 and 33have the following physical properties:

DENSITY: R FACTOR: COMPRESSIVE STRENGTH: WATER ABSORPTION: CLOSED CELL CONTENT: DIMENSIONAL STABILITY:	2.8 pounds per cubic foot, fro 7.00 37 psi (parallel) 2.3% >90%	ee rise	ASTM D1622 ASTM C518 ASTM D1621 ASTM D2842 ASTM D2856 ASTM D2126
% Volume Change, 158° F, 100% Humidity. 2 wks -4.00% % Volume Change, -20° F, 7 days -2.00%			
HIGH TEMPERATURE TOLERANCE 250° F LOW TEMPERATURE TOLERANCE -250° F			
FLAMESPREAD:	E -250 F N/A		ASTM E84
SMOKE DEVELOPED:	N/A		ASTM E84
YIELD: System 10 System 33	10 cubic feet or 120 square feet at 1" thickness 33 cubic feet or 396 square feet @ 1" thickness		
TACK FREE TIME:	30 seconds		
RISE TIME:	30 seconds		