





EL 462-A



ETF 492-A







MICROPlumb® PRODUCTS Infrared Shower Control



Description

Infrared sensor-activated, electronic shower control for a single, pre-mixed shower. System includes six components: ETF 492-A EL 154, MCR 139-A, ETF 458-A, EL 462-A and AC-460.

Specifications

- Infrared sensor module, controller, solenoid, 120 VAC/24 VAC transformer, 20' power cord kit and mounting hardware for sensor and controller
- Water-proof (NEMA 6) sensor module
- Operates on 24 VAC
- Visible LED target detection
- Adjustable sensing range
- Adjustable run time
- 24 VAC brass body solenoid with integral "Y" strainer
- Diagnostic LED indicators in control module
- Control module may be located remotely as far as 35' from sensor using additional MICROPlumb® extension cord kits
- RJ-11 modular connections from sensor and solenoid to controller
- AC-460 Act-O-Matic® self-cleaning institutional security-style shower head; access behind the wall required for installation

Accessories

ETF 1003-72
ETF 1003-108
ETF 1003-240
Single Wire Extension Cord Kit
Single Wire Extension Cord Kit
Single Wire Extension Cord Kit

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



10500 Seymour Avenue • Franklin Park, Illinois 60131-1259 Phone 800-671-6970 • Fax 847-671-6944